

配管用鋼管(SGP)				
呼称	インチ	外径	肉厚	kg/m
6A	1/8	10.5	2.0	0.419
8A	1/4	13.8	2.3	0.652
10A	3/8	17.3	2.3	0.851
15A	1/2	21.7	2.8	1.31
20A	3/4	27.2	2.8	1.68
25A	1	34.0	3.2	2.43
32A	1 1/4	42.7	3.5	3.38
40A	1 1/2	48.6	3.5	3.89
50A	2	60.5	3.8	5.31
65A	2 1/2	76.3	4.2	7.47
80A	3	89.1	4.2	8.79
90A	3 1/2	101.6	4.2	10.1
100A	4	114.3	4.5	12.2
125A	5	139.8	4.5	15.0
150A	6	165.2	5.0	19.8
175A	7	190.7	5.3	24.2
200A	8	216.3	5.8	30.1
225A	9	241.8	6.2	36.0
250A	10	267.4	6.6	42.4
300A	12	318.5	6.9	53.0
350A	14	355.6	7.9	67.7
400A	16	406.4	7.9	77.6
450A	18	457.2	7.9	87.5
500A	20	508.0	7.9	97.4

一般構造用鋼管(STK)													
外径	インチ	肉厚	kg/m		外径	インチ	肉厚	kg/m		外径	インチ	肉厚	kg/m
21.7	1/2	1.9	0.928		216.3	8	4.5	23.5		558.8	22	6.4	87.2
27.2	3/4	1.9	1.19				5.8	30.1				7.9	107
2.3		1.41	8.2				42.1	9.5				129	
34.0	1	2.3	1.80				12.7	63.8				12.7	171
		3.2	2.43		16.0	214							
42.7	1 1/4	2.3	2.29		241.8	9	6.2	36.0		609.6	24	6.4	95.2
		3.5	3.38		267.4	10	5.8	37.4				7.9	117
48.6	1 1/2	2.3	2.63				6.6	42.4				9.5	141
		3.2	3.58				9.3	59.2				12.7	187
60.5	2	2.3	3.30				318.5	12		6.0	46.2	16.0	234
		2.8	3.98		6.9	53.0				19.0	277		
		3.2	4.52		7.9	60.5				22.0	319		
		3.8	5.31		9.5	72.4				660.4	26	6.4	103
76.3	2 1/2	2.8	5.08		10.3	78.3	7.9	127					
		3.2	5.77		12.7	95.8	9.5	152					
		4.2	7.47		355.6	14	6.4	55.1				12.7	203
89.1	3	2.8	5.96				7.9	67.7		711.2	28	6.4	111
		3.2	6.78				9.5	81.1				7.9	137
		4.2	8.79				11.1	94.3				9.5	164
		5.5	11.3		12.7	107	12.7	219					
101.6	3 1/2	3.2	7.76		406.4	16	6.4	63.1		16.0	274		
		3.5	8.47				7.9	77.6		762.0	30	7.9	147
		4.2	10.1				9.5	93.0				9.5	176
		5.7	13.5				12.7	123				12.7	235
114.3	4	3.5	9.56			16.0	154	812.8	32			8.0	159
		4.5	12.2			19.0	182			9.5	188		
		6.0	16.0			457.2	18			6.4	71.1	12.7	251
127.0	4 1/2	4.5	13.6	7.9	87.5					16.0	314		
		139.8	5	3.5	11.8			9.5	105	914.4	36	8.0	179
				4.0	13.4			12.7	139			9.5	212
				4.5	15.0	16.0	174	12.7	282				
6.6	21.7			19.0	205	16.0	354						
152.4	5 1/2	5.0	18.2	508.0	20	6.4	79.2	1016.0	40	9.5	236		
165.2	6	3.7	14.7			7.9	97.4			12.7	314		
		4.5	17.8			9.5	117			16.0	395		
		5.0	19.8			12.7	155			1219.2	48	9.5	283
		7.1	27.7			16.0	194	12.7	378				
190.7	7	5.3	24.2			19.0	229	16.0	475				

機械構造用鋼管(STKM11A)						
外径	肉厚	kg/m		外径	肉厚	kg/m
6.0	1.0	0.123		31.8	1.2	0.906
7.0	1.0	0.148			1.6	1.19
8.0	1.0	0.173			2.0	1.47
9.0	1.0	0.197			2.3	1.67
9.5	1.0	0.210			34.0	1.2
	1.2	0.246		1.6		1.28
10.0	1.0	0.222		2.0		1.58
	1.2	0.260		2.3		1.80
	1.6	0.331		3.2		2.43
11.0	1.0	0.247		35.0	1.2	1.00
12.0	1.0	0.271		38.1	1.2	1.09
	1.2	0.320			1.6	1.44
	1.6	0.410			2.0	1.78
12.7	1.0	0.289			2.3	2.03
	1.2	0.340			42.7	1.2
	1.6	0.438		1.6		1.62
14.0	1.0	0.321		2.3		2.29
	15.9	1.2		0.435		3.5
1.6		0.564		45.0		1.6
2.0		0.686			2.0	2.12
19.1	1.2	0.530		48.6	1.6	1.85
	1.6	0.690			2.3	2.63
	2.0	0.843			3.5	3.89
21.7	2.8	1.31			50.8	1.2
22.2	1.2	0.621		1.6		1.94
	1.6	0.813		2.0		2.41
	2.0	0.996		2.3		2.75
25.4	1.2	0.716		54.0		1.6
	1.6	0.939		60.5	1.6	2.32
	2.0	1.15			2.0	2.89
	2.3	1.31	63.5	1.6	2.44	
	3.2	1.75	70.0	1.6	2.70	
27.2	2.8	1.68	76.3	1.6	2.95	
28.6	1.2	0.811		2.0	3.66	
	1.6	1.07	89.1	1.6	3.45	
	2.0	1.31	101.6	1.6	3.95	

株式会社 吉 田 商 店

TEL 029-254-6811

FAX 029-254-6814